

## Motor driven plunger metering pump



Motor-driven plunger dosing pump, mechanical actuated, PRIUS combines efficiency and chemical resistance to a wide capacity range for an extensive number of applications.

- Single or three phase motor power supply
- **Ceramic or Stainless Steel plunger**
- Aluminium enclosure
- Double ball check valve
- Tropicalized three-phase motors



## Identification code

CUSTOM.      PACKAGING      INTERNAL

P P 0 0 0 1 0 0 2 4 D V 1 2 0 0 N 0 0 0

BAR      L/H      COLOR

CAPACITY	
50 Hz	60 Hz
010024	24 l/h @ 10 bar
010013	13 l/h @ 10 bar
010010	10 l/h @ 10 bar
010005	5 l/h @ 10 bar
010080	80 l/h @ 10 bar
010043	43 l/h @ 10 bar
010032	32 l/h @ 10 bar
010016	16 l/h @ 10 bar
010130	130 l/h @ 10 bar
010070	70 l/h @ 10 bar
010052	52 l/h @ 10 bar
010026	26 l/h @ 10 bar
010210	210 l/h @ 10 bar
010113	113 l/h @ 10 bar
010084	84 l/h @ 10 bar
010042	42 l/h @ 10 bar
010320	320 l/h @ 10 bar
010172	172 l/h @ 10 bar
010128	128 l/h @ 10 bar
010064	64 l/h @ 10 bar
007508	508 l/h @ 7 bar
007273	273 l/h @ 7 bar
007203	203 l/h @ 7 bar
007101	101 l/h @ 7 bar
010023	23 l/h @ 10 bar
010011	11 l/h @ 10 bar
010005	5 l/h @ 10 bar
010076	76 l/h @ 10 bar
010038	38 l/h @ 10 bar
010019	126 l/h @ 10 bar
010126	126 l/h @ 10 bar
010063	63 l/h @ 10 bar
010031	31 l/h @ 10 bar
010195	195 l/h @ 10 bar
010097	97 l/h @ 10 bar
010048	48 l/h @ 10 bar
010300	300 l/h @ 10 bar
010150	150 l/h @ 10 bar
010075	75 l/h @ 10 bar
007469	469 l/h @ 7 bar
007234	234 l/h @ 7 bar
007117	117 l/h @ 7 bar

MATERIAL pump head + plunger	
D	PP + CERAMIC (SIALOX 96)
E	SS (AISI316L) + SS (AISI420)

MOTOR	POWER SUPPLY	PHASE
1	0,18Kw 220-240/380-420 - 50 Hz	3-PHASE
2	0,37Kw 220-240/380-420 - 50 Hz	3-PHASE
3	0,18Kw 220/380 - 60 Hz	3-PHASE
4	0,37Kw 220/380 - 60 Hz	3-PHASE

REDUCTION GEAR	
1	8:1
2	15:1
4	20:1

O RING	
V	FKM B
D	Dutral
W	WAX

LUBRICANT TYPE	
BRAND	MODEL
MOBIL	MOBILGEAR 632
SHELL	OMALA OIL 320
BP	ENERGOL GR-XP 320
IP	MELLANA OIL 320
ESSO	SPARTAN EP 320
AGIP	BLASIA 320

## Motor driven plunger metering pump

### “PRIUS P” SERIES - 50 Hz / 3-PHASE MOTOR

#### Features

- Aluminium enclosure
- Ceramic (SIALOX96 ) piston and PP pump head or SS (AISI420) pump head and piston
- Power supply: 220-240/380-420 V - Δ/Y connection
- Environment temperature: ..... -10-40 °C (14-104 °F)
- Chemical temperature with SS pump head: ..... -10-90 °C (14-194 °F)\*
- Chemical temperature with PP pump head: ..... -10-40 °C (14-104 °F)
- Installation class ..... II
- Pollution level ..... 2
- Audible noise..... 78 dbA (± 5 dB)
- Protection degree ..... IP 55
- Max suction height ..... 3 m
- Oil capacity..... 0,3 lt (Refer to “Lubricant type” table)

\* The specified temperature can be exceeded temporarily (max 15') for sterilization or flushing with hot water.

#### MOTORS

0,18 kW: 3-phase 230 V 1350 rpm

0,37 kW: 3-phase 230 V 1370 rpm

**PRIUS P - PP PUMP HEAD**



**PRIUS P - SS PUMP HEAD**



## Motor driven plunger metering pump

### PRIUS P WITH PP PUMP HEAD AND CERAMIC PLUNGER 50 HZ / 3-PHASE MOTOR

PRIUS P 50 Hz								
stroke length	PLUNGER diam. (mm)	PRIUS P 50 Hz	Stroke/1'	Pressure bar	Capacity l/h	Motor	HOSES CONNECTION	INSTALLATION KIT
							PP	
15 mm	14	010024	175	10	24	0,18 kW	G1/2" 12x18	A
		010013	94		13			
		010010	70		10			
		010005	35		5			
	25	010080	175	10	80	0,18 kW	G1/2" 12x18	A
		010043	94		43			
		010032	70		32			
		010016	35		16			
	32	010130	175	10	130	0,18 kW	G1/2" 12x18	A
		010070	94		70			
		010052	70		52			
		010026	35		26			
	40	010210	175	10	210	0,37 kW	G3/4" d.i. 18 mm	B
		010113	94		113			
		010084	70		84			
		010042	35		42			
	50	010320	175	10	320	0,37 kW	G3/4" d.i. 18 mm	B
		010172	94		172			
		010128	70		128			
		010064	35		64			

#### ACCESSORIES

##### A. INSTALLATION KIT INCLUDED

- 1/2" foot filter with 13 mm (int. diam.) hose fitting
- 3/4" injection valve
- 13 x16 PVDF or 12 X 18 PVC delivery hose
- 13 x16 PVDF or 12 X 18 PVC suction hose

##### B. INSTALLATION KIT (OPTION)

- 1 1/2" foot filter with 18 mm (int. diam.) hose fitting (G1 1/2" - 18 mm)
- 1 1/2" injection valve

##### C. INSTALLATION KIT (OPTION)

- 1 1/2" foot filter with 32 mm (int. diam.) hose fitting (G1 1/2" - 32 mm)
- 1 1/2" injection valve

## Motor driven plunger metering pump

### PRIUS P WITH SS PUMP HEAD AND PLUNGER 50 HZ / 3-PHASE MOTOR

Stainless Steel pump does not fit installation kit.

PRIUS P 50 Hz							
stroke length	PLUNGER diam. (mm)	PRIUS P 50 Hz	Stroke/1'	Pressure bar	Capacity l/h	Motor	HOSES CONNECTION
							SS
15 mm	14	010024	175	10	24	0,18 kW	R1/2"
		010013	94		13		
		010010	70		10		
		010005	35		5		
	25	010080	175	10	80	0,18 kW	R1/2"
		010043	94		43		
		010032	70		32		
		010016	35		16		
	32	010130	175	10	130	0,18 kW	R1/2"
		010070	94		70		
		010052	70		52		
		010026	35		26		
	40	010210	175	10	210	0,37 kW	R3/4"
		010113	94		113		
		010084	70		84		
		010042	35		42		
	50	010320	175	10	320	0,37 kW	R3/4"
		010172	94		172		
		010128	70		128		
		010064	35		64		
63	007508	175	7	508	0,55 kW	R1"	
	007273	94		273	0,37 kW		
	007203	70		203			
	007101	35		101			

## Motor driven plunger metering pump

### PRIUS P WITH PP PUMP HEAD AND CERAMIC PLUNGER 60 HZ / 3-PHASE MOTOR

PRIUS P 60 Hz								
stroke length	PLUNGER diam. (mm)	PRIUS P 60 Hz	Stroke/1'	Pressure bar	Capacity l/h	Motor	HOSES CONNECTION	INSTALLATION KIT
							PP	
15 mm	14	010023	175	10	23	0,18 kW	G1/2" 12x18	A
		010011	87		11			
		010005	44		5			
	25	010076	175	10	76	0,18 kW	G1/2" 12x18	A
		010038	87		38			
		010019	44		19			
	32	010126	175	10	126	0,18 kW	G1/2" 12x18	A
		010063	87		63			
		010031	44		31			
	40	010195	175	10	195	0,37 kW	G3/4" d.i. 18 mm	B
		010097	87		97			
		010048	44		48			
	50	010300	175	10	300	0,37 kW	G3/4" d.i. 18 mm	B
		010150	87		150			
		010075	44		75			

### PRIUS P WITH SS PUMP HEAD AND PLUNGER 60 HZ / 3-PHASE MOTOR

PRIUS P 60 Hz							
stroke length	PLUNGER diam. (mm)	PRIUS P 60 Hz	Stroke/1'	Pressure bar	Capacity l/h	Motor	HOSES CONNECTION
							SS
15 mm	14	010023	175	10	23	0,18 kW	R1/2"
		010011	87		11		
		010005	44		5		
	25	010076	175	10	76	0,18 kW	R1/2"
		010038	87		38		
		010019	44		19		
	32	010126	175	10	126	0,18 kW	R1/2"
		010063	87		63		
		010031	44		31		
	40	010195	175	10	195	0,37 kW	R3/4"
		010097	87		97		
		010048	44		48		
	50	010300	175	10	300	0,37 kW	R3/4"
		010150	87		150		
		010075	44		75		
	63	007469	175	7	469	0,55 kW	R1"
		007234	87		234	0,37 kW	
		007117	44		117		